



ASME CLASS 150 SERVICE PRESSURE/TEMP. RATINGS

*Limited to Gasket & Glass Material

Temp. (°F)	Pressure (PSIG)	
	CS	316SS
-20 to 100	285	275
150	270	255
200	260	235
250	245	225
300	230	215
350	215	205
400	200	195
450	185	180
500	170	170

*Consult Sales for Higher & Lower Temps.

REVISIONS			
Rev.	Modification	Date	Done By
0	Original	2/9/2016	WAS
A	Note for Retainer Material	6/20/2016	WAS
B	8" Unit Removed for Separate Drawing	9/9/2016	WAS
C	Added Note on Nuts, and Nameplate Information, NACE Note	2/3/2017	WAS

BILL OF MATERIALS						
* - Denotes an Optional, Non-Standard Material						
No.	Name of Part	Qty.	Material	Max. Temp. (°F)	Material Grade	
Wetted	011	1	Carbon Steel		ASTM A-216 WCB	
			316SS		ASTM A-351 CF8M	
	007	2	Neoprene	250		
			Gylon®	500	Gylon® 3504	
			*EPDM	250		
			*Viton®	350		
			*Graphite	500		
*Non Asbestos	500	Klinger C-4400				
*Buna-N	250					
048	Lens	2	Tempered Boro.	500		
171	Drip Tube	1	316SS			
Non-Wetted	008	Cushion	2	Non-Asbestos	500	Klinger C-4400
	001	2	Steel		ASTM A-216 WCB	
			316SS		ASTM A-351 CF8M	
	137	8	Plated Steel		SAE Gr. 5	
			*316SS		ASTM A193-B8M	
004	8	Plated Steel		SAE Gr. 5		
		*316SS		ASTM A194-8M		
163	Nameplate	1	SS			

Notes:

1. Retainers & Body are the Same Material
2. For 4" & 6" Sizes, Studs Thread Directly to Body (No Nuts)
3. For NACE Compliance, Please Inquire

PRODUCT SPECIFICATIONS								
Flange Size	A		B		C		Weight	
	In.	mm.	In.	mm.	In.	mm.	lbs.	kg.
1/2 & 3/4	4-5/8	117	1-1/4	32	4-3/16	106	6	2.7
1	5-5/8	143	1-1/4	32	4-1/8	105	11	5.0
1-1/2	6-1/2	165	1-3/4	44	5-3/8	137	17	7.7
2	7-7/8	200	2	51	6-1/8	156	27	12.2
3	9-3/8	238	3-3/16	81	7-3/4	197	56	25.4
4 ₂	11	279	4-3/8	111	10-5/8	270	75	34.0
6 ₂	14-1/4	362	6-7/8	175	12-3/4	324	150	68.0

S14FC Series Configuration Choices:

Reference the Series S14FC Model Number Matrix on our Website or Inquire with our Sales Team

Gylon® is a Registered Trademark of Garlock Sealing Technologies
 Viton® is a Registered Trademark of The Chemours Company

JOHN C ERNST LLC.			www.JOHNERNST.com 21 Gail Ct. Sparta, N.J. USA	
Series F14FC Sight Flow Indicator - Drip Tube - 150# Flanged				
Sheet 1 of 1	Drawn By WAS	Tolerances, unless otherwise noted Dec.: ± Frac.: ± Ang.: ±		Size: A
Scale: NTS	Approved By: JCW			
Date: 03-FEB-17	Dwg. No.: SC2.S14FC.04.0.0			Rev. C